

CALPICO INC
 1387 San Mateo Ave.
 SO. SAN FRANCISCO, CA 94080
 Phone: 650-588-2241
 FAX: 650-873-6952

Adhesive backed underground marking tape for direct placement onto pipe or cable. This tape is available in all of the approved APWA color codes for respective line identification.

This tape is 3" wide, and is available in 300-foot long, or 1,000-foot long rolls.

PHYSICAL PROPERTIES - HP 260 Polypropylene Tape

	Standard	Metric	ASTM Test Method
Adhesion to Stainless Steel	44 oz/in width	75 N/10 mm	D 3330 D 3330M
Thickness	1.9 mils	.05 mm	D 3652 D 3652M
Elongation	130 %	130 %	D 3759 D 3759M
Service Temperature Min	20 °F	-7 °C	N/A
Service Temperature Max	150 °F	66 °C	N/A
Application Temperature Min	35 °F	2 °C	N/A
Application Temperature Max	110 °F	43 °C	N/A
Tensile Strength (longitudinal direction)	27 lbs/in width	47.3 N/10 mm	D 3759 D 3759M
Tensile Strength (transverse direction)	44 lbs/in width	4.82 N/10 mm	D 3759 D 3759M
Holding Power to Fiberboard	10,000 minutes	10,000 minutes	PSTC 107